

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 054 019 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

22.11.2000 Bulletin 2000/47

(51) Int. Cl. 7: **C08B 11/08, A61K 9/20**

(21) Application number: **00304109.2**

(22) Date of filing: **16.05.2000**

(84) Designated Contracting States:

**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: **18.05.1999 JP 13678799**

(71) Applicant:

**SHIN-ETSU CHEMICAL CO., LTD.
Chiyoda-ku Tokyo (JP)**

(72) Inventor:

**Obara, Sakae,
Specialty Chemicals Research Center
Kubiki-mura Naka Kubiki-gun, Niigata-ken (JP)**

(74) Representative:

**Goddard, David John et al
Harrison Goddard Foote,
1 Stockport Road,
Marple
Stockport SK6 6BD (GB)**

(54) **Low-substituted hydroxypropyl cellulose**

(57) The present invention provides low-substituted hydroxypropyl cellulose exhibiting good granulation characteristics and tablet properties. Specifically, there is provided low-substituted hydroxypropyl cellulose having a hydroxypropoxyl content in the range of 5.0 to 16.0% by weight and an apparent average degree of polymerization in the range of 350 to 700.

EP 1 054 019 A1

Description

BACKGROUND OF THE INVENTION

1. Field of the invention

[0001] This invention relates to low-substituted hydroxypropyl cellulose having good granulation characteristics and tablet properties.

2. Description of the related art

[0002] Hydroxypropyl cellulose is a nonionic polymer derived from cellulose by etherifying hydroxyl groups of its constitutional glucose ($C_6H_{10}O_5$) units with hydroxypropyl groups, and is being used in a wide field of application owing to its diverse characteristics.

[0003] Generally, hydroxypropyl cellulose is a compound having a hydroxypropoxyl content of 50 to 80% by weight. A compound having a hydroxypropoxyl content of 5.0 to 16.0% by weight is called "low-substituted hydroxypropyl cellulose", and its properties are different from those of ordinary hydroxypropyl cellulose.

[0004] One difference between them lies in solubility in water. Specifically, hydroxypropyl cellulose is soluble in water, whereas low-substituted hydroxypropyl cellulose is insoluble in water but swells by absorption of water. By taking advantage of this property, low-substituted hydroxypropyl cellulose is used chiefly as a disintegrator for oral solid pharmaceutical preparations.

[0005] Moreover, since low-substituted hydroxypropyl cellulose is in fibrous form and hence serves to increase the hardness of tablets, it can be used as a dry binder. Furthermore, since its kneaded mixture with water has binding properties, it can also be used as a wet binder.

SUMMARY OF THE INVENTION

[0006] Generally, wet granulation is employed to improve the fluidity of a raw powder material having poor fluidity. However, the properties (i.e., particle size distribution and strength) of the resulting granular product, as well as the hardness and disintegrability of tablets formed therefrom, are primarily affected by the properties of the binder.

[0007] In the case of low-substituted hydroxypropyl cellulose, its degree of substitution and particle size have been considered to be important factors affecting its binding properties. However, it has frequently been recognized that, even if these factors are controlled, the disintegration of tablets may be delayed as a result of abnormally advanced granulation, or the hardness of tablets may be reduced as a result of unsatisfactory granulation characteristics.

[0008] In order to overcome these disadvantages of the prior art, the present inventors made intensive investigations and have now found that the degree of polymerization or molecular weight of low-substituted hydroxypropyl cellulose affects its binding properties in wet granulation. The present invention has been completed on the basis of this finding.

[0009] The present invention provides low-substituted hydroxypropyl cellulose having a hydroxypropoxyl content in the range of 5.0 to 16.0% by weight and an apparent average degree of polymerization in the range of 350 to 700.

[0010] Good granulation characteristics and tablet properties can be obtained by using the low-substituted hydroxypropyl cellulose of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0011] The present invention is more specifically described hereinbelow.

[0012] The low-substituted hydroxypropyl cellulose of the present invention has a hydroxypropoxyl content in the range of 5.0 to 16.0% by weight.

[0013] The hydroxypropoxyl content can be determined according to the method of quantitative determination described in the Japanese Pharmacopoeia under the head of "Low-substituted Hydroxypropyl Cellulose".

[0014] The apparent average degree of polymerization of the low-substituted hydroxypropyl cellulose of the present invention is explained below:

[0015] It is generally known that the degree of polymerization (or molecular weight) of a binder affects its binding power. This is believed to be due to the fact that a common binder exhibits a binding effect by dissolving in a solvent such as water, and the viscosity of the resulting solution depends on the degree of polymerization. However, since low-substituted hydroxypropyl cellulose does not dissolve in the solvent even in the case of wet granulation, its degree of polymerization has not been considered to be directly related to its granulation characteristics. Accordingly, no investigation has yet been made as to the relationship between the degree of polymerization (or molecular weight) and the

granulation characteristics of low-substituted hydroxypropyl cellulose.

[0016] The present inventors have surprisingly found that low-substituted hydroxypropyl cellulose having a specific degree of polymerization offers stable granulation characteristics, even though it does not dissolve in solvents. The reason for this is believed to be that low-substituted hydroxypropyl cellulose exhibits its binding properties by a mechanism different from that of common binders.

[0017] In the present invention, the apparent average degree of polymerization of low-substituted hydroxypropyl cellulose is defined to be a value calculated as the average degree of polymerization when it is determined according to a method similar to the method for determining the average degree of polymerization of cellulose (pulp) constituting the raw material for low-substituted hydroxypropyl cellulose as described in the official compendium (ASTM D1795-62).

[0018] This method comprises obtaining a relative viscosity from the kinematic viscosity of a solution of a sample in a cupri-ethylenediamine reagent solution and the kinematic viscosity of the solvent, calculating an intrinsic viscosity therefrom, and multiplying it by a factor to determine the average degree of polymerization. Since the factor used in this method is the factor defined for cellulose, it is necessary to define another factor for low-substituted hydroxypropyl cellulose. However, low-substituted hydroxypropyl cellulose is a compound into which only a slight quantity of substituent groups are introduced. Accordingly, on the assumption that there will be no significant difference as compared with cellulose, the apparent average degree of polymerization is determined by using the factor for cellulose directly.

[0019] The low-substituted hydroxypropyl cellulose of the present invention has an apparent average degree of polymerization in the range of 350 to 700 and preferably 400 to 600. The apparent average degree of polymerization can be controlled suitably by degree of polymerization for the starting material, reaction temperature, reaction time, and other process parameters in the process for preparing the low-substituted hydroxypropyl cellulose. If the apparent average degree of polymerization is less than 350, granulation by stirring may be advanced to an abnormal extent, resulting in an increased strength of the granular product and hence a prolonged disintegration time of the tablets formed therefrom. On the other hand, if the apparent average degree of polymerization is greater than 700, granulation may not proceed satisfactorily, resulting in an insufficient strength of the granular product and hence an insufficient hardness of the tablets formed therefrom.

[0020] In addition to the above-described properties, the low-substituted hydroxypropyl cellulose of the present invention preferably has a volume-average particle size (diameter) of 10 to 100 μm in use of a dry type laser diffraction method. If the average particle size is less than this range, the low-substituted hydroxypropyl cellulose has been pulverized so vigorously that it may be difficult to maintain the apparent average degree of polymerization in the range of 350 to 700 and, therefore, its binding properties may be abnormally enhanced in wet granulation. On the other hand, if the average particle size is greater than this range, the low-substituted hydroxypropyl cellulose may be unsuitable for wet granulation. The dry type laser diffraction method means the method wherein the volume-average particle size is measured based on the diffraction intensity when the laser is applied to the powders which has been jetted by a compressed air. A laser diffraction type particle size analyzer manufactured by Rodos & Helos, Inc. is exemplified. According to, for example, page 88 of "Kaitei Zoho Funtai Bussei Zusesu" (revised and enlarged edition of Illustration of Powder Properties" edited by Funtai Kogakukai and Nippon Funtai Kogyogijutsu Koyokai, published by Nikkei Gijutsu-Tosho Co., Ltd., 1985, the volume-average particle size is calculated by $\{\sum(nD^3)/\sum n\}^{1/3}$ wherein D is a particle diameter; n is the number of particles having the particle diameter; and $\sum n$ is a total number of particles.

[0021] Moreover, the bulk density (densified) is preferably in the range of 0.4 to 0.8 g/ml. If the bulk density (densified) is less than 0.4 g/ml, the low-substituted hydroxypropyl cellulose may have poor fluidity and be hence unsuitable for practical purposes. On the other hand, if the bulk density (densified) is greater than 0.8 g/ml, the low-substituted hydroxypropyl cellulose may fail to achieve a sufficient hardness during compaction.

[0022] The bulk density can be measured in the following manner. A sample is uniformly fed, from 23 cm above, into a cylindrical vessel having a diameter of 5.03 cm and a height of 5.03 cm (hence a volume of 100 ml) through a JIS (Japanese Industrial standard) 22-mesh (710 μm) screen. After its upper surface is leveled, the vessel is fitted with a special-purpose cap supplied together with the powder tester by Hosokawa Micron Corporation, and the powder is added up to its upper edge. Then, the vessel is tapped 180 times from a tapping height of 1.8 cm. Thereafter, the cap is removed and the powder is leveled at the upper edge of the vessel and weighed. The measured value obtained in this state is regarded as the bulk density. This procedure can be carried out by use of the powder tester (PT-D) manufactured by Hosokawa Micron Corporation.

[0023] No particular limitation is placed on the method for granulating the low-substituted hydroxypropyl cellulose of the present invention, and any well-known method may be employed.

[0024] Similarly, no particular limitation is placed on the method for forming the low-substituted hydroxypropyl cellulose of the present invention into tablets, and any well-known method may be employed.

[0025] In addition to the low-substituted hydroxypropyl cellulose of the present invention, the tablets may contain, for example, active ingredients, lubricants (e.g., magnesium stearate), excipients (e.g., corn starch and lactose), and other disintegrators and binders. Although no particular limitation is placed on the content of the low-substituted hydroxypropyl cellulose of the present invention in the tablets, it is preferably in the range of 5 to 50% by weight.

[0026] The present invention is more specifically explained with reference to the following examples and comparative examples. However, these examples are not to be construed to limit the scope of the invention.

Example 1

[0027] Wood pulp was soaked in a 49 wt% aqueous solution of sodium hydroxide and then pressed to obtain alkali cellulose. Eight hundred grams (800 g) of this alkali cellulose was charged into a reactor, and its atmosphere was replaced with nitrogen. After the addition of 85.6 g of propylene oxide, the resulting mixture was reacted, with stirring, at 40°C for 1 hour and then at 70°C for 1 hour. The reaction mixture was poured into a 5 litre double-arm kneader containing 2 litres of hot water at 65°C, kneaded therewith for about 10 minutes, and neutralized with acetic acid to crystallize the reaction product. This reaction product was washed with hot water at 90°C, dehydrated by pressing, dried, and then pulverized with a high-speed rotary impact pulverizer to obtain a low-substituted hydroxypropyl cellulose having a hydroxypropoxyl content of 11.0% by weight and an apparent average degree of polymerization of 530.

Examples 2-5 and Comparative Examples 1-3

[0028] Low-substituted hydroxypropyl celluloses were prepared in the same manner as in Example 1, except that the hydroxypropoxyl content and the apparent average degree of polymerization were varied. The results thus obtained are shown in Table 1.

[0029] With respect to the low-substituted hydroxypropyl celluloses obtained in the foregoing examples and comparative examples, measurements were made under the following conditions.

1) Granulation by stirring

[0030] 70% by weight of lactose and 30% by weight of a low-substituted hydroxypropyl cellulose were mixed, and 200 g of the mixture was placed in a stirring granulation apparatus (Vertical Granulator VG-25, manufactured by Powrex Corporation) and subjected to stirring granulation by using hydroxypropyl cellulose (140 g of a 1 wt% aqueous solution of HPC-L, manufactured by Nippon Soda Co., Ltd.) as the binder. The granular product was dried by allowing it to stand at 60°C overnight. The particle size distribution of the granular product was analyzed by sieving and used to determine the average particle size.

2) Tableting test

[0031] The granular product was blended with 0.5% by weight of magnesium stearate, and this blend was formed (under a tableting pressure of 1 metric ton) into tablets (8 mm in diameter) by means of a rotary tablet machine. The hardness of the tablets was measured with an Erweka hardness tester, and the disintegration time thereof was measured according to the method described in the Japanese Pharmacopoeia. The results thus obtained are shown in Table 1.

Table 1

	Low-substituted hydroxypropyl cellulose				Granulation		Tablets	
	Hydroxypropoxyl Content (wt%) (Note 1)	Apparent average degree of polymerization (Note 2)	Average particle size (μm) (Note 3)	Bulk density (densified) (g/ml)	Observation on granulation	Average particle size of granular product (μm)	Hardness of tablets (kgf)	Disintegration time of tablets (min.)
Example 1	11.0	530	37	0.55	Good	150	5.2	5
Example 2	11.1	353	38	0.54	Good	180	5.5	5
Example 3	11.1	697	37	0.52	Good	120	4.8	4
Example 4	5.1	528	38	0.51	Good	120	4.8	4
Example 5	13.9	522	39	0.56	Good	190	6.0	5
Comparative Example 1	11.1	310	37	0.53	Excessive granulation	750	9.8	20
Comparative Example 2	11.0	810	38	0.51	Insufficient granulation	80	1.5	1
Comparative Example 3	11.0	730	38	0.52	Insufficient granulation	85	1.9	1

(Note 1) "Hydroxypropoxyl content" was determined according to the Japanese Pharmacopoeia.

(Note 2) "Apparent average degree of polymerization" was determined according to ASTM D1795-62.

(Note 3) "Average particle size of granular product" was measured with a laser diffraction type particle size analyzer manufactured by Rodos & Helos, Inc.

[0032] As can be seen from Table 1, low-substituted hydroxypropyl cellulose having an apparent average degree of polymerization adjusted to a value of 350 to 700 offers good granulation characteristics and tablet properties.

Claims

1. Low-substituted hydroxypropyl cellulose having a hydroxypropoxyl content in the range of 5.0 to 16.0% by weight and an apparent average degree of polymerization in the range of 350 to 700.
2. Low-substituted hydroxypropyl cellulose according to Claim 1 having said apparent average degree of polymerization in the range of 400 to 600.
3. Low-substituted hydroxypropyl cellulose according to Claim 1 or 2, further having a volume-average particle size of 10 to 100 μm in use of a dry type laser diffraction method.
4. Low-substituted hydroxypropyl cellulose according to any one of Claims 1 to 3, further having a densified bulk density in the range of 0.4 to 0.8 g/ml.
5. Low-substituted hydroxypropyl cellulose according to any of Claims 1, 2 or 4, further having a volume-average particle size of 10 to 100 μm as measured by a dry type laser diffraction method.
6. Low-substituted hydroxypropyl cellulose according to any of Claims 1, 2 or 4, further having a volume-average particle size of 10 to 100 μm .
7. A tablet containing the low-substituted hydroxypropyl cellulose according to any preceding claim.
8. A tablet according to Claim 7 containing 5 to 50 % by weight of the low-substituted hydroxypropyl cellulose.



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 30 4109

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (InCL.7)
X	US 4 091 205 A (ONDA YOSHIRO ET AL) 23 May 1978 (1978-05-23) * example 1 *	1-8	C08B11/08 A61K9/20
X	PATENT ABSTRACTS OF JAPAN vol. 1996, no. 04, 30 April 1996 (1996-04-30) & JP 07 324101 A (SHIN ETSU CHEM CO LTD), 12 December 1995 (1995-12-12) * abstract; example 1 *	1-8	
X	PATENT ABSTRACTS OF JAPAN vol. 1999, no. 01, 29 January 1999 (1999-01-29) & JP 10 279601 A (SHIN ETSU CHEM CO LTD), 20 October 1998 (1998-10-20) * abstract; examples 1-8; table 1 *	1-8	
X	US 5 200 194 A (EDGREN DAVID E ET AL) 6 April 1993 (1993-04-06) * column 6, line 55-59; examples 1,2 *	1-8	
X	WO 97 03654 A (SANDOZ AG ;HAEBERLIN BARBARA (CH); SANDOZ LTD (CH); RICHTER FRIEDR) 6 February 1997 (1997-02-06) * page 4, line 7-10 *	1-8	
			TECHNICAL FIELDS SEARCHED (InCL.7)
			C08B A61K
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 13 September 2000	Examiner Radke, M
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPF FORM 1503 03 82 (P04C01)

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 00 30 4109

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

13-09-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4091205 A	23-05-1978	JP 1158448 C	25-07-1983
		JP 51063927 A	02-06-1976
		JP 57053100 B	11-11-1982
		AU 8691775 A	02-06-1977
		BE 836021 A	16-03-1976
		CA 1042878 A	21-11-1978
		CH 619719 A	15-10-1980
		DE 2553239 A	12-08-1976
		FR 2304353 A	15-10-1976
		GB 1479557 A	13-07-1977
		IT 1050310 B	10-03-1981
		NL 7513391 A, B,	01-06-1976
		SE 430165 B	24-10-1983
		SE 7512627 A	31-05-1976
JP 07324101 A	12-12-1995	JP 2994956 B	27-12-1999
JP 10279601 A	20-10-1998	NONE	
US 5200194 A	06-04-1993	AT 133561 T	15-02-1996
		AU 3333393 A	19-07-1993
		DE 69208104 D	14-03-1996
		DE 69208104 T	30-05-1996
		DK 617611 T	20-05-1996
		EP 0617611 A	05-10-1994
		ES 2082626 T	16-03-1996
		JP 7506806 T	27-07-1995
		MX 9207402 A	01-07-1993
		WO 9311748 A	24-06-1993
		ZA 9209848 A	13-01-1994
WO 9703654 A	06-02-1997	AU 706174 B	10-06-1999
		AU 6615296 A	18-02-1997
		BE 1009856 A	07-10-1997
		BR 9609537 A	23-02-1999
		CA 2225960 A	06-02-1997
		CN 1195289 A	07-10-1998
		CZ 9800091 A	15-04-1998
		EP 0839028 A	06-05-1998
		FR 2736550 A	17-01-1997
		HU 9900391 A	28-06-1999
		IT RM960501 A	12-01-1998
		JP 11509223 T	17-08-1999
		NO 980081 A	08-01-1998
		NZ 313633 A	28-05-1999
		PL 324502 A	25-05-1998

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 00 30 4109

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

13-09-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9703654 A		SK 4498 A	06-05-1998
		US 6004973 A	21-12-1999

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

120

121

122

123

124

125

126

127

128

129

130

131

132

133

134

135

136

137

138

139

140

141

142

143

144

145

146

147

148

149

150

151

152

153

154

155

156

157

158

159

160

161

162

163

164

165

166

167

168

169

170

171

172

173

174

175

176

177

178

179

180

181

182

183

184

185

186

187

188

189

190

191

192

193

194

195

196

197

198

199

200